

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product information

Trade name : ARALDITE AV 4738

Use : Resin for adhesive systems

Company : Huntsman Advanced Materials (Europe)BVBA
Everslaan 45
3078 Everberg / Belgium

Telephone : +41619661599
Telefax : +41619661589
Emergency telephone number : +32 35 751 234 (in France ORFILA : +33(0)145425959)

For further Product EHS related questions concerning this document or its contents, please contact:
E-Mail: global_product_ehs_admat@huntsman.com

2. HAZARDS IDENTIFICATION

Irritating to eyes and skin.
May cause sensitization by skin contact.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Formulated epoxy resin preparation

Hazardous components

Chemical Name	CAS-No.	Symbol(s):	R-phrased(s)	Concentration [%]
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight < 700)	25068-38-6	Xi, N	R36/38 R43 R51/53	25.00 - 40.00
epoxy phenol novolak resin	28064-14-4	Xi, N	R36/38 R43 R51/53	10.00 - 25.00
trimethylolpropane triglycidyl ether EC-No.: 222-384-0	3454-29-3	Xi	R36/38 R43 R52/53	1.00 - 10.00
diglycidylether of polypropyleneglycol	26142-30-3	Xi	R36/38 R43	1.00 - 5.00

4. FIRST AID MEASURES

Inhalation : Move to fresh air.
Call a physician immediately.

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

- Eye contact : Rinse immediately with plenty of water for at least 15 minutes.
If eye irritation persists, consult a specialist.
- Skin contact : Wash off immediately with soap and plenty of water.
If skin irritation persists, call a physician.
- Ingestion : Immediately give plenty of water (if possible charcoal slurry).
Do not induce vomiting.
Obtain medical attention.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray.
Carbon dioxide (CO₂).
Foam.
Dry powder.
- Extinguishing media which must not be used for safety reasons : High volume water jet.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and protective suit.
- Further information : Burning produces obnoxious and toxic fumes.
Carbon oxides.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Keep away from sources of ignition - No smoking.
Avoid contact with skin, eyes and clothing.
Do not breathe vapours/dust.
- Environmental precautions : Prevent product from entering drains.
Do not contaminate surface water.
Avoid subsoil penetration.
- Methods for cleaning up : Soak up with inert absorbent material and dispose of as hazardous waste.

7. HANDLING AND STORAGE

Handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Handle and open container with care.

Storage

- Further information on storage conditions : Keep away from food, drink and animal feeding stuffs.
Keep container tightly closed.
Keep at temperatures between 2 and 40 °C.

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

Storage hazard class : Storage class 10, Environmentally hazardous liquids
Huntsman Advanced
Materials

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Control parameters	Update	Basis
------------	---------	--------------------	--------	-------

Engineering measures

No special precautions required.

Personal protective equipment

- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.
Filter type AX-P2 (organic vapours, particles)
- Eye protection : Tightly fitting safety goggles.
- Hand protection : Material of gloves for long term application (BTT>480 min):
Butyl rubber
Ethyl Vinyl Alcohol Laminate (EVAL)
Material of gloves for short term/splash application (10 min<BTT<480 min):
Nitrile rubber
Neoprene rubber
Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US).
Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers.
Additional information can be found for instance at www.gisbau.de
- Skin and body protection : long sleeved clothing
- Hygiene measures : Keep away from food, drink and animal feeding stuffs.
Wash hands before breaks and immediately after handling the product.
- Protective measures : Keep away from sources of ignition - No smoking.
Avoid contact with skin, eyes and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : paste
- Colour : light grey

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

Odour	: slight
Boiling point	: > 200 °C
Thermal decomposition	: > 200 °C
Flash point	: > 200 °C Method: DIN 51758 (Pensky-Martens Closed Cup)
Vapour pressure	: < 10 Pa at 20 °C
Density	: 1.5 g/cm ³ at 25 °C
Water solubility	: at 20 °C Note: practically insoluble
Miscibility with water	: immiscible at 20 °C
Viscosity, dynamic	: 600 - 1,000 Pa.s at 25 °C

10. STABILITY AND REACTIVITY

Conditions to avoid	: Note: Take necessary action to avoid static electricity discharge.
Materials to avoid	: Strong acids and strong bases. Strong oxidizing agents.
Hazardous decomposition products	: Carbon oxides. Burning produces obnoxious and toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: LD50 rat Dose: > 5,000 mg/kg
Eye irritation	: irritating rabbit
Skin irritation	: irritating rabbit dermal
Sensitization	: Causes sensitization. guinea pig dermal

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

Biodegradability : Result: Not readily biodegradable.

Ecotoxicity effects

Further information on ecology

Additional ecological information : Avoid subsoil penetration.
Prevent product from entering drains.
Do not contaminate surface water.

13. DISPOSAL CONSIDERATIONS

Product : Waste Key Number: 070208
Must be incinerated, when in compliance with local regulations.

Container : Empty containers can be landfilled after cleaning, when in compliance with the Environmental Protection (Duty of Care) Regulations 1991.

14. TRANSPORT INFORMATION

Land transport

ADR:

UN-No: 3082
Class: 9
Classification code: M6
Packaging group: III
Risk No.: 90
ADR/RID-Labels: 9
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
contains: EPOXY RESIN

RID:

UN-No: 3082
Class: 9
Packaging group: III
Risk No.: 90
ADR/RID-Labels: 9
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
contains: EPOXY RESIN

Sea transport

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

IMDG:

UN-No: 3082
Class: 9
Packaging group: III
ADR/RID-Labels: 9
MFAG:
EmS: F-A S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
contains: (EPOXY RESIN)

Air transport

IATA-DGR:

UN/ID No.: UN 3082
Class: 9
Packaging group: III
Packing instruction (cargo aircraft): 914
Max. Qty/Pack.: 450.00 L
(999.00 = No limit)
Packing instruction (passenger aircraft): 914
Max. Qty/Pack.: 450.00 L
(999.00 = No limit)
ADR/RID-Labels: 9
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
contains: (EPOXY RESIN)

15. REGULATORY INFORMATION

Labelling according to EEC Directive

Labelling required

Symbol(s):	: Xi N	Irritant Dangerous for the environment
R-phrased(s)	: R36/38 R43 R51/53	Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S-phrased(s)	: S28 S36/37/39 S61	After contact with skin, wash immediately with plenty of soap and water. Wear suitable protective clothing, gloves and eye/face protection. Avoid release to the environment. Refer to special instructions/safety data sheets.

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

Exceptional labelling of special preparations : Contains epoxy constituents. See information supplied by the manufacturer.

Hazardous components which must be listed on the label : reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight < 700)

epoxy phenol novolak resin

trimethylolpropane triglycidyl ether
EC-No.: 222-384-0

National legislation

Notification status

: EINECS yes

: TSCA yes

: DSL yes

: AICS yes

: KECI (KR) yes

: ENCS (JP) yes

: INV (CN) yes

: PICCS (PH) yes

16. OTHER INFORMATION

List of R-phrases (Section 3)

Ident-No: ARALDITE AV 4738

Version 3
Revision Date 02.04.2009

Print Date 09.05.2009

R36/38	Irritating to eyes and skin.
R43	May cause sensitization by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974. Users of products supplied by Huntsman Advanced Materials should take appropriate measures to ensure working practices are in accordance with the Control of Substances Hazardous to Health Regulations (COSHH).

All information is based on results gained from experience and tests and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry out sufficient tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressly agreed in writing nor construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Huntsman Advanced Materials General Conditions of Sale.