# **SAFETY DATA SHEET**



HARDENER HV 4739

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

#### Identification of the substance or mixture

Product name Product type Product description Use of the substance/mixture	:	HARDENER HV 4739 Liquid. Preparation Hardener for adhesive systems
Supplier	:	Huntsman Advanced Materials (Europe)BVBA Everslaan 45 3078 Everberg / Belgium Tel.: +41 61 299 20 41 Fax: +41 61 299 20 40
Emergency telephone number	:	EUROPE: +32 35 75 1234 France ORFILA: +33(0)145425959 ASIA: +65 6336-6011 China: +86 20 39377888 Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1/800/424.9300

For further Product EHS related questions concerning this document or its contents, please contact

E-Mail: global\_product\_ehs\_admat@ huntsman.com

### 2. HAZARDS IDENTIFICATION

2

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	: Xn; R21 C; R34 R43 R52/53
Human health hazards	: Harmful in contact with skin. Causes burns. May cause sensitisation by skin contact.
Environmental hazards	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 11 for more detailed information on health effects and symptoms.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient name	CAS number	%	Number	Classification		
triethylenetetramine	112-24-3	13 - 30		Xn; R21 [1] C; R34 R43 R52/53		
4,4'-methylenebis(cyclohexylamine)	1761-71-3	3 - 7		Xn; R22 [1] C; R35 N; R51/53		
See section 16 for the full text of the R-phrases declared above						

Date of issue/Date of revision

: 10/7/2010.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in Section 8.

### 4. FIRST AID MEASURES

First-aid measures	
Inhalation	: Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Ingestion	: Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	: Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
See Section 11 for more det	ailed information on health offects and symptoms

See Section 11 for more detailed information on health effects and symptoms.

### 5. FIRE-FIGHTING MEASURES

Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: In a fire or if heated, a pressure increase will occur and the container may burst.

# 5. FIRE-FIGHTING MEASURES

		Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	-	Burning produces obnoxious and toxic fumes., Carbon oxides, Nitrogen oxides
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	-	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.
Methods for cleaning up		
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

# 7. HANDLING AND STORAGE

Handling	: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative mad from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.	
Storage	: Store between the following temperatures: 2 to 40°C (35.6 to 104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (se section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.	e
Storage hazard class Huntsman Advanced Materials	: Storage class 8, Corrosive substances	
Packaging materials		
Date of issue/Date of revision	: 10/7/2010. <b>3</b>	/9

Wellmid Electronics (Shenzhen) Co., Ltd. Web: www.wellmid.com Email: wellmid@wellmid.com Tel: 86-755-28168941 Fax: 86-755-22648848

# 7. HANDLING AND STORAGE

Recommended

: Use original container.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values	
Ingredient name	Occupational exposure limits
No exposure limit value know	).
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.
Exposure controls	
Occupational exposure controls	: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and th safe working limits of the selected respirator.
Hand protection	: Material of gloves for long term application (BTT>480min):
	(BTT = Break Through Time)
	Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber
	Material of gloves for short term/splash application (10min <btt<480min): nitrile rubber</btt<480min): 
	Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US). Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers. Additional information can be found for instance at www.gisbau.de.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Skin protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist befor handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# Date of issue/Date of revision

Wellmid Electronics (Shenzhen) Co., Ltd. Web: www.wellmid.com Email: wellmid@wellmid.com Tel: 86-755-28168941 Fax: 86-755-22648848

# 9. PHYSICAL AND CHEMICAL PROPERTIES

General information			
Appearance			
Physical state	: Liquid. [Paste.]		
Colour	: White to grey		
Odour	: Amine-like.		
Important health, safety a	nd environmental information		
Boiling point	: >200°C (>392°F)		
Flash point	: Closed cup: >100°C (>212°F) [DIN 51758 EN 22719 (Per	nsky-Mar	tens Closed Cup)]
Decomposition temperature	: >200°C (>392°F)		
Vapour pressure	: <0.01 kPa (<0.075 mm Hg) [20°C]	20	deg C
Density	: 1.8 g/cm <sup>3</sup> [25°C (77°F)]		
Water solubility	: partially soluble		
Viscosity	: Dynamic: 42000 to 64000 mPa·s (42000 to 64000 cP)	25	deg C

# **10. STABILITY AND REACTIVITY**

Chemical stability	The product is stable.	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur	
Conditions to avoid	No specific data.	
Materials to avoid	strong acids, strong bases, strong oxidising agents	
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.	S
	Burning produces obnoxious and toxic fumes Carbon oxides. Nitrogen oxides	

# **11. TOXICOLOGICAL INFORMATION**

<b>Toxicokinetics</b>					
Absorption	:	Not available.			
Distribution	:	Not available.			
Metabolism	:	Not available.			
Elimination	:	Not available.			
Potential acute health effects	<u>s</u>				
Inhalation	:	May give off gas, vapor or d system. Exposure to decon effects may be delayed follo	nposition products		
Ingestion	1	May cause burns to mouth,	throat and stoma	ch.	
Skin contact	1	Corrosive to the skin. Causes burns. Harmful in contact with skin. May cause sensitisation by skin contact.			
Eye contact	1	Corrosive to eyes. Causes	burns.		
Acute toxicity					
Product/ingredient name HARDENER HV 4739		<mark>Result</mark> LD50 Dermal LD50 Oral	<b>Species</b> Rat Rat	<mark>Dose</mark> <2000 mg/kg >2000 mg/kg	Exposure - -
<b>Conclusion/Summary</b>	:	Not available.			
Potential chronic health effe	<u>cts</u>				
Chronic toxicity					
<b>Conclusion/Summary</b>	1	Not available.			
Irritation/Corrosion					
<b>Conclusion/Summary</b>	1	Not available.			
<u>Sensitiser</u>					

Date of issue/Date of: 10/7/2010.5/9revision

# **11. TOXICOLOGICAL INFORMATION**

Product/ingredient name		Route of exposure	Species	Result	
HARDENER HV 4739		skin	Guinea pig	Sensitising	
Conclusion/Summary	: N	lot available.			
Carcinogenicity					
<b>Conclusion/Summary</b>	: N	lot available.			
<u>Mutagenicity</u>					
<b>Conclusion/Summary</b>	: N	lot available.			
<b>Teratogenicity</b>					
<b>Conclusion/Summary</b>	: N	lot available.			
Reproductive toxicity					
<b>Conclusion/Summary</b>	: N	lot available.			
Chronic effects		Once sensitized, a severe ery low levels.	allergic reaction m	ay occur when subsequently exposed to	
Carcinogenicity	: N	: No known significant effects or critical hazards.			
Mutagenicity	: N	No known significant effects or critical hazards.			
Teratogenicity	: N	No known significant effects or critical hazards.			
Developmental effects	: N	No known significant effects or critical hazards.			
Fertility effects	: N	No known significant effects or critical hazards.			
Over-exposure signs/sympto	<u>ms</u>				
Inhalation	: N	lo specific data.			
Ingestion		Adverse symptoms may in tomach pains	clude the following	j:	
Skin	p r	Adverse symptoms may in pain or irritation edness vlistering may occur	clude the following	j:	
Eyes	p v	Adverse symptoms may in pain vatering edness	clude the following	j:	

#### **12. ECOLOGICAL INFORMATION**

Environmental effects	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Aquatic ecotoxicity	
<b>Conclusion/Summary</b>	: Not available.
<b>Biodegradability</b>	
<b>Conclusion/Summary</b>	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

### **13. DISPOSAL CONSIDERATIONS**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **13. DISPOSAL CONSIDERATIONS**

European waste catalogue ( EWC)	: The relevant EU Directives and local, regional and national regulations must be complied with. It is among the tasks of the end user to assign the waste to waste codes specific to industrial sectors and processes according to the European Waste catalogue. It is recommended that the details be agreed with the waste disposer responsible.	
	07 02 04*	
	07 02 04* other organic solvents, washing liquids and mother liquors	
Hazardous waste	: Yes.	

### **14. TRANSPORT INFORMATION**

#### International transport regulations

#### Proper shipping name

ADR	1	Amines, liquid, corrosive, n.o.s. 4,4'-METHYLENEBIS(CYCLOHEXYLAMINE) TRIETHYLENE TETRAMINE	

: Amines, liquid, corrosive, n.o.s. (4,4'-METHYLENEBIS(CYCLOHEXYLAMINE)) (TRIETHYLENE IMDG TETRAMINE)

**IATA** : Amines, liquid, corrosive, n.o.s. (4,4'-METHYLENEBIS(CYCLOHEXYLAMINE)) (TRIETHYLENE **TETRAMINE**)


Regulatory information	UN number	Classes	Packing group	Label	Additional information
Land - road/ railway ADR/RID Class	UN2735	8	11		Classification code C7 Hazard identification 80 number
Sea IMDG Class	UN2735	8	II	8	<u>Emergency schedules (EmS)</u> F-A, S-B
Air IATA Class	UN2735	8	11	8	Passenger and Cargo Aircraft Quantity limitation: 1 L Packaging instructions: 808 <u>Cargo Aircraft Only</u> Quantity limitation: 30 L Packaging instructions: 812

### **15. REGULATORY INFORMATION**

#### **EU regulations**

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC ( including amendments) and take into account the intended product use.

Hazard symbol or symbols



2

**Risk phrases** 

: R21- Harmful in contact with skin.

R34- Causes burns.

R43- May cause sensitisation by skin contact.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Date of issue/Date of	: 10/7/2010.	7/9
revision		

## **15. REGULATORY INFORMATION**

Safety phrases	: S26- In case of contact with eyes, rinse immediately with plenty of water and seek
	medical advice.
	S36/37/39- Wear suitable protective clothing, gloves and eye/face protection. S45- In case of accident or if you feel unwell, seek medical advice immediately (show
	the label where possible).
Contains	: triethylenetetramine
	4,4'-methylenebis(cyclohexylamine)
International regulations	
International lists	
Europe inventory	: All components are listed or exempted.
United States inventory (	: All components are listed or exempted.
TSCA 8b)	
Canada inventory	: All components are listed or exempted.
Australia inventory (AICS)	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Japan inventory (ENCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Philippines inventory ( PICCS)	: All components are listed or exempted.

# **16. OTHER INFORMATION**

Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)	<ul> <li>R21- Harmful in contact with skin.</li> <li>R22- Harmful if swallowed.</li> <li>R34- Causes burns.</li> <li>R35- Causes severe burns.</li> <li>R43- May cause sensitisation by skin contact.</li> <li>R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</li> <li>R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</li> </ul>
Full text of classifications referred to in sections 2 and 3 - United Kingdom (UK)	: C - Corrosive Xn - Harmful N - Dangerous for the environment

#### References

Epoxy Resins and Curing Agents; Toxicology, Health, Safety and Environmental Aspects (Plastics Europe, May 2006) The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974.

Users of products supplied by Huntsman Advanced Materials should take appropriate measures to ensure working practices are in accordance with the Control of Substances Hazardous to Health Regulations (COSHH).

<u>History</u>	
Date of printing	: 10/7/2010.
Date of issue/ Date of revision	: 10/7/2010.
Date of previous issue	: No previous validation.
Version	: 1

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

Date of issue/Date of	: 10/7/2010.	8/9
revision		

#### **16. OTHER INFORMATION**

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

Enquiries should be addressed to your nearest Huntsman sales office or to:

Huntsman Belgium (BVBA) Everslaan 45 B-3078 Everberg Belgium Tel.:+32-(0)2-758-9211

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.