

Ident-No: XD 4467 POLYOL

Version 3
Revision Date 20.03.2009

Print Date 09.04.2009

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product information

Trade name : XD 4467 POLYOL

Use : Polyol for adhesive systems

Company : Huntsman Advanced Materials (Europe)BVBA
Everslaan 45
3078 Everberg / Belgium

Telephone : +41619661599
Telefax : +41619661589
Emergency telephone number : +32 35 751 234 (in France ORFILA : +33(0)145425959)

For further Product EHS related questions concerning this document or its contents, please contact:
E-Mail: global_product_ehs_admat@huntsman.com

2. HAZARDS IDENTIFICATION

The product contains no substances classified as hazardous to health in concentrations which should be taken into account according to EC directive.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Formulated polyol preparation

4. FIRST AID MEASURES

Inhalation : Move to fresh air.
If symptoms persist, call a physician.

Eye contact : Rinse immediately with plenty of water for at least 15 minutes.
If eye irritation persists, consult a specialist.

Skin contact : Wash off with soap and plenty of water.
If skin irritation persists, call a physician.

Ingestion : Immediately give plenty of water (if possible charcoal slurry).
Obtain medical attention.
Do not induce vomiting.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing : Water spray.

Ident-No: XD 4467 POLYOL

Version 3
Revision Date 20.03.2009

Print Date 09.04.2009

media Carbon dioxide (CO₂).
Foam.
Dry powder.

Extinguishing media which must not be used for safety reasons : High volume water jet.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and protective suit.

Further information : Burning produces obnoxious and toxic fumes.
Carbon oxides.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Do not breathe vapours/dust.
Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation.

Environmental precautions : Do not allow material to contaminate ground water system.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

7. HANDLING AND STORAGE

Handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Handle and open container with care.

Storage

Further information on storage conditions : Keep away from food, drink and animal feeding stuffs.
Keep container tightly closed.
Keep at temperatures between 2 and 40 °C.

Storage hazard class : Storage class 12, Liquids, not dangerous
Huntsman Advanced
Materials

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Control parameters	Update	Basis
------------	---------	--------------------	--------	-------

Personal protective equipment

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.

Ident-No: XD 4467 POLYOL

Version 3
Revision Date 20.03.2009

Print Date 09.04.2009

- Filter type AX-P2 (organic vapours, particles)
- Eye protection : Tightly fitting safety goggles.
- Eye protection : Tightly fitting safety goggles.
- Hand protection : Material of gloves for long term application (BTT>480 min):
Butyl rubber
Ethyl Vinyl Alcohol Laminate (EVAL)
Nitrile rubber
Neoprene rubber
Polyvinyl Chloride (PVC)
Material of gloves for short term/splash application (10 min<BTT<480 min):
Butyl rubber
Ethyl Vinyl Alcohol Laminate (EVAL)
Nitrile rubber
Neoprene rubber
Polyvinyl Chloride (PVC)
Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US).
Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers.
Additional information can be found for instance at www.gisbau.de
- Skin and body protection : long sleeved clothing
- Skin and body protection : long sleeved clothing
- Hygiene measures : Keep away from food, drink and animal feeding stuffs.
Wash hands before breaks and immediately after handling the product.
- Hygiene measures : Keep away from food, drink and animal feeding stuffs.
Wash hands before breaks and immediately after handling the product.
- Protective measures : Avoid contact with skin, eyes and clothing.
- Protective measures : Avoid contact with skin, eyes and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : liquid
- Colour : beige
- Odour : oily
- Thermal decomposition : > 200 °C
- Flash point : > 100 °C

Ident-No: XD 4467 POLYOL

Version 3
Revision Date 20.03.2009

Print Date 09.04.2009

Method: DIN 51758 (Pensky-Martens Closed Cup)

Density : 1.4 g/cm³
at 25 °C

Water solubility : at 20 °C
Note: practically insoluble

Miscibility with water : immiscible
at 20 °C

Viscosity, dynamic : 1.3 - 2.6 Pa.s
at 25 °C

10. STABILITY AND REACTIVITY

Conditions to avoid : Note: Take necessary action to avoid static electricity discharge.

Materials to avoid : Strong acids and strong bases.
Strong oxidizing agents.

Hazardous decomposition products : Burning produces obnoxious and toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50 rat
Dose: > 5,000 mg/kg

Eye irritation : No eye irritation
rabbit

Skin irritation : No skin irritation
rabbit
dermal

Sensitization : none
guinea pig
dermal

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Further information on ecology

Additional ecological information : Avoid subsoil penetration.
Prevent product from entering drains.
Do not contaminate surface water.

Ident-No: XD 4467 POLYOL

Version 3
Revision Date 20.03.2009

Print Date 09.04.2009

13. DISPOSAL CONSIDERATIONS

- Product : Must be incinerated, when in compliance with local regulations.
- Container : Empty containers can be landfilled after cleaning, when in compliance with the Environmental Protection (Duty of Care) Regulations 1991.
- Contaminated packaging : Waste Key Number: 305055

14. TRANSPORT INFORMATION

Land transport

ADR:

Regulation: Not dangerous goods

RID:

Regulation: Not dangerous goods

Sea transport

IMDG:

Regulation: Not dangerous goods

Air transport

IATA-DGR:

Regulation: Not dangerous goods

15. REGULATORY INFORMATION

Labelling according to EEC Directive

No labelling required

National legislation

Water contaminating class : 1 slightly water endangering
(self-assessment)

Notification status

: EINECS yes

Ident-No: XD 4467 POLYOL

Version 3
Revision Date 20.03.2009

Print Date 09.04.2009

: TSCA yes

16. OTHER INFORMATION

All information is based on results gained from experience and tests and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry out sufficient tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressly agreed in writing nor construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Huntsman Advanced Materials General Conditions of Sale.